

GRESOL LUBRICANTS

BARODA GREASES AND AUTO CARE PRODUCTS PVT. LTD
SINCE 1994

GRESOTRANS OIL TQ

All vehicles fitted with automatic transmission and power steering where Type A – Suffix A fluid is used.

All new generation automotive vehicle fitted with synchromesh gear boxes and Z.F. power steering gear boxes. It is also applicable for earth moving vehicles.

Meets:

TES-122, TEMPL 03/ZF

Recommended For:

All vehicles fitted with automatic transmission & power steering where Type A-Suffix A fluid is used. All modern automotive vehicles fitted with synchromesh gear boxes & Z.F. power steering gear boxes.

Benefits:

- Reduces friction and wear even in extreme pressure
- Low temperature fluidity
- Good stability and resistance to foaming
- Good thermal and oxidation resistance
- Protection against corrosion

Pack Size:

205lts, 50lts, 20lts, 5lts, 1lt

Characteristics

Sr.	Properties	TQ
1.	Kin. Viscosity cSt @100 c	7.4 – 8.2
2.	V.I. (min)	155
3.	Flash Point (coc) c , min	210
4.	Pour Point c, max	(-) 24

Note: The specification are subjected to Variations/Continuous Improvement/ Customization

IT'S AUTO ENGINEERS CHOICE