

GRESOL LUBRICANTS
BARODA GREASES AND AUTO CARE PRODUCTS PVT. LTD
SINCE 1994

HYDRAULIC OIL

GRESOL HYDRO 32/46/68/100/150/320/460

INTRODUCTION

GRESOL HYDRO grade oils are formulated from highly refined base Stock using selected anti-oxidant, anti wear, anti-rust and anti-foam additives.

ADVANTAGES

- **Tailor made viscosity to suit hydraulic systems.**
- **Good film strength**
- **Resists wear & tear**
- **Good demulsibility**
- **Anti corrosive**
- **Anti rusting**
- **Anti foaming**
- **Good oxidation stability**

APPLICATIONS

GRESOL HYDRO grades are recommended for use in hydraulic systems, enclosed gear box, chain drives, compressors, vaccum pumps, mining machinery, machine tools oil circulating systems. Also used in antifriction bearings of electric motors.

TYPICAL SPECIFICATIONS

Characteristics	32	46	68	100	150	320	460
1. Appearance Bright & Clear						
2.Colour(ASTM)	3	3	3	3	3	3	33.
3.Viscosity at 40 Deg. C	29-35	41-50	61-75	90-110	125-165	288-352	414-506
4.Viscosity Index	95	95	95	95	95	90	90
5.Flash Point Deg.C	190	200	210	210	230	230	250
6.Pour Point Deg.C	-6	-6	-6	-6	-6	6	6
7.Zinc % 0.3	0.3	0.3	0.3	0.3	0.3	0.3	
8.Standard	IS-10522 - 1983 ISO – VG						

Pack Size:

210 ltrs, 50ltrs, 20ltrs, 10ltrs, 5ltrs

IT'S AUTO ENGINEERS CHOICE