

**GRESOL LUBRICANTS**  
BARODA GREASES AND AUTO CARE PRODUCTS PVT. LTD  
SINCE 1994

## REFRIGERATION OIL

### GRESOL REFRIN 32/46/68

GRESOL Refrin oils are formulated from specially selected lube base stocks. These oils are Fortified with anti foaming, anti sealing additives.

#### ADVANTAGES

- Low pour point to prevent congealing.
- Low cloud point to withstand extreme low temperature without flocculating wax.
- Good chemical stability.
- Liquefied refrigerant to prevent deposition.

#### APPLICATIONS

GRESOL Refrin grade oils are recommended for use in evaporation and compressor of Refrigeration system.

#### TYPICAL SPECIFICATIONS

Characteristics	32	46	68
1. Colour (ASTM)	3	3	3
2. Viscosity at 40 deg.C CST	29-35	41-50	61-75
3. Flash point deg.C	185	200	220
4. Pour point deg. C	-48	-27	-27
5. Copper corrosion	1A	1A	1A

#### EQUIVALENTS

GRESOL	I.O.C.	H.P.	B.P.	CASTROL
Refrin 32	Servofriz 32	-	Frezol 32	Hed Ref Oil
Refrin 46	Servofriz 46	Seetful 46	Frezol 46	Castrol Ref Oilr
Refrin 68	Servofriz 68	Seetful 68	Frezol 68	-

#### Pack Size:

**210 ltrs, 50ltrs, 20ltrs**

*IT'S AUTO ENGINEERS CHOICE*