

HEAT TREATMENT OIL : QUENCHING OIL

Meets: IS 2664 : 1980, IS 4543 : 1977

PRODUCT & TECHNICAL DATA SHEET



Gresol Lubricants

Product Name: **GRESO QUENCH - QUENCHING OIL**

DESCRIPTION

ISO VG : 68/22/32/220/460
High quality oil blended from high viscosity index mineral oil and possesses good inherent oxidation stability.

APPLICATION

This oil is used as quenching medium in general heat treatment application where tower quenching speed is desired.

PERFORMANCE BENEFITS

- Tailor made viscosity to suit hydraulic systems.
- Good Film Strength.
- Resists wear and tear.
- Good Demulsibility.
- Anti-Corrosive.
- Anti-Rusting.
- Anti-Forming.
- Good Oxidation Stability.

PERFORMANCE STANDARDS

Meets Followings Specifications

- IS 2664 : 1980
- IS 4543 : 1977

LEADING QUENCHING OIL MANUFACTURER IN INDIA

For further information please contact :

Baroda Greases And Autocare Products Pvt. Ltd, Gujarat, India

Email: info@gresollubricants.com, the.gresol1994@gmail.com

Ph:+912653253565M:+919638384647



HEAT TREATMENT OIL : QUENCHING OIL

Meets: IS 2664 : 1980, IS 4543 : 1977

PRODUCT & TECHNICAL DATA SHEET



Gresol Lubricants

Technical Detail:

Specification	Kinematic Viscosity at 40 C est	VI	Flash Point C CoC, Min	Pour Point Deg C
Quench 68	68.5	101	252	-6
Quench 22	22.3	102	192	-9
Quench 32	32.1	100	196	-9
Quench 220	18.1	94	250	-3
Quench 460	31.7	92	290	-3

Note: The specification are subjected to Variations/Continuous Improvement/ Customization

Available Packing:

210 ltrs Barrel	50ltrs HPDE Drum	20ltrs HPDE Bucket

Above Product commonly known as

Quenching oil,Heat Treatment Oil,Heat Treatment Fluid.

LEADING QUENCHING OIL MANUFACTURER IN INDIA

For further information please contact :

Baroda Greases And Autocare Products Pvt. Ltd, Gujarat, India

Email: info@gresollubricants.com, the.gresol1994@gmail.com

Ph:+912653253565M:+919638384647

